
PRODUCT DATASHEET

Wafer Butterfly Valve

For water, steam, air, oil and light chemicals.

DUCTILE IRON • ALUMINUM BRONZE • DN40–DN300 • PN16 up to DN300 • EN1092-2 PN10/16/150LB/10K





Technical features

- Concentric
- Mounting pad: ISO 5211
- Lloyds Register type Approval • TÜV
- Available with lever, gearbox, pneumatic or electric actuator

Technical performance

Design: EN593
Flanges: EN 1092-1
Pressure testing: EN 12266-1
Rating: DN40–200 PN16 / DN200–DN300 PN16
Shell / Seat PN16: 2.4 / 1.8 MPa
Shell / Seat PN10: 1.5 / 1.1 MPa
Gas seat test: 0.6 MPa
Temperature: –10°C to +80°C
Coating: RAL5026, 250 µm

Materials

Part	Material
Body	EN-GJS-400-18-LT / JS1025 Ductile iron
Stem	2205 Duplex
Disc	C95400 Aluminum Bronze alloy
Seat	NBR
O-ring	NBR
Shaft Sleeve	GF/PE
Pin	AISI 316
Lockable handle	Aluminum
Gearbox option (1)	Ductile Iron IP65
Gearbox option (2)	Ductile Iron IP67

Valve specifications

DN	PN	D (mm)	C (mm)	n × d (mm)	L Face to face (mm)	Top Flange	Weight (kg)
40	PN16	150	110	4 × Ø19	43	F05 □ 9mm	1,5
50	PN16	165	125	4 × Ø19	43	F05 □ 9mm	2,8
65	PN16	185	145	4 × Ø19	46	F05 □ 9mm	3,7
80	PN16	200	160	4 × Ø19	46	F05 □ 9mm	4
100	PN16	220	180	4 × Ø19	52	F07 □ 11mm	5,4
125	PN16	250	210	4 × Ø19	56	F07 □ 14mm	7,5
150	PN16	285	240	4 × Ø23	56	F07 □ 14mm	9,5
200	PN16	340	295	4 × Ø23	60	F10 □ 17mm	14
250	PN16	395	350	4 × Ø28	68	F10 □ 22mm	21
300	PN16	445	400	4 × Ø28	78	F10 □ 22mm	33

PPS International BV • De Zwingel 7B • 4926DC Lage Zwaluwe • The Netherlands
+31 (0)168 712400 • sales@pps-nl.com • www.pps-nl.com