
PPS

PRODUCT DATASHEET

Gate Valve

For water, steam, air, oil and light chemicals.

DUCTILE IRON • STAINLESS STEEL • DN40–DN300 • PN16 up to DN200 • PN10 DN200 and larger





Technical features

- Non Rising Stem
- Bolted Bonnet, Short Type F4
- Including position indicator
- Full bore, Bi-directional flow
- Lloyds Register type Approval

Technical performance

Design: EN 1171
Flanges: EN 1092-2 – Raised face
Face to Face: EN 558
Pressure testing: EN 12266-1 RATE B
Rating: DN40–200 PN16 / DN200–300 PN10
Shell / Seat PN16: 2.4 / 1.8 MPa
Shell / Seat PN10: 1.5 / 1.1 MPa
Gas seat test: 0.6 MPa
Temperature: -10°C to +120°C
Coating: RAL5026, 150 µm

Materials

Part	Material
Body + Bonnet	EN-GJS-400-18-LT / JS1025 Ductile iron
Stem	1.4021 / AISI 420 Stainless Steel
Wedge (≤100)	1.4021 / AISI 420 Stainless Steel
Wedge (≥125)	EN-GJS-400-18-LT / JS1025 Ductile iron
Packing	PTFE
Sealing gasket	Graphite
Seat Ring	1.4301 / AISI 304 Stainless Steel
Indicator	1.4301 / AISI 304 Stainless Steel
Stuffing Box	EN-GJS-400-15 / JS1030 Ductile iron
Handwheel	EN-GJL-250 / Cast iron

Valve specifications

DN	PN	H (mm)	D (mm)	D1 PCD (mm)	n × d (mm)	L Face to face (mm)	Weight (kg)
40	PN16	255	150	110	4 × Ø19	140	9
50	PN16	300	165	125	4 × Ø19	150	10
65	PN16	325	185	145	4 × Ø19	170	12
80	PN16	385	200	160	8 × Ø19	180	16
100	PN16	440	220	180	8 × Ø19	190	20
125	PN16	480	250	210	8 × Ø19	200	33
150	PN16	540	285	240	8 × Ø23	210	43
200	PN16	638	340	295	12 × Ø23	230	65
200	PN10	638	340	295	8 × Ø23	230	65
250	PN10	770	390	350	12 × Ø23	250	100
300	PN10	880	445	400	12 × Ø23	270	142

PPS International BV • De Zwingel 7B • 4926DC Lage Zwaluwe • The Netherlands
+31 (0)168 712400 • sales@pps-nl.com • www.pps-nl.com